

LED driver - not dimmable, 1-19W



Technical data

Primary voltage	220-240VAC 50/60 Hz
System effect	1-19W
Secondary amperage	350mA
Min. load	1W
Max. load	19W
Efficiency	+83%
Vout range	2-54 Vdc
Max. voltage (open circuit)	≤60 Vdc
Expected lifespan	50,000 hours
Dimmable	No
Flicker free	Yes, according to the latest Ecodesign / ErP directive
Fuse	Built-in thermal fuse with auto reset
Distribution box on secondary side	Yes, with 6 outputs
Cable from the secondary side	Yes, 15 cm to distribution box
Connection cable on primary side	Yes, 2 m cable equipped with 2P plug
Possibility of attachment	Yes, using screws (not included)
Dimensions driver	L: 116 mm, W: 41 mm, H: 25 mm
Dimensions distribution box	L: 58 mm, B: 37 mm, H: 10 mm
Ambient temperature range ta	-20° - +45°
Storage temperature range	-20° - +70°
Mains switching cycles	>100,000
Leakage current	0.45mA
IP rating	IP20
Insulation class	Class II, SELV
Material	Plastic
Environment	Indoor
Warranty	5 years
Approvals	CE

Product information

- LED driver for cabinet lighting and mini downlights (350mA, 6 outputs)
- Built-in thermofuse with auto reset
- Quick and easy installation
- Can be fastened by screws
- Do NOT plug in any LED lamps, when connected to power



Max. LED driver per circuit breaker

Circuit breaker	B10	B13	B16	C10	C13	C16
Max. number	14	23	28	37	48	59

Item no.	EAN no.	Type
98514026	5704629004993	dimmable

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.